

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

PD25509

**WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.**

**NOTE: Before installing, consult local electrical codes for wiring and grounding requirements.**

1. Attach two screws to the cross bar, then secure them with two lock nuts. Adjust the length of the screws if necessary.
2. Attach the cross bar to the outlet box by using two mounting screws.
3. Choose the length of the chain you need, then weave the fixture wire and the fixture grounding wire through the chain. Then connect one end link of the chain with the loop by using the loop lock.
4. Connect the other end of the chain link to the top loop by using the loop lock.
5. Thread the fixture wire and fixture grounding wire through the top loop, canopy and cross bar.
6. Pull out the outlet wires and the house grounding wire from the outlet box. Make wire connections using the wire nuts:
  - The smooth wire (marked) from the fixture to the black wire from the power source.
  - The ridged wire (unmarked) from the fixture to the white wire from the power source.
  - Attach the fixture grounding wire to the mounting strap with the green grounding screw. Then connect it to the house grounding wire with a wire nut.Carefully tuck the wires back into the outlet box.
7. Attach the canopy to the cross bar by inserting two screws, then secure it with two bolt nuts.
8. Install a bulb (not included). See relamping label at socket area or packaging for maximum allowed wattage.
9. Fix the glass shade to the fitter by threading the set screws onto the glass notch.
10. Turn on the power at the main fuse or circuit breaker box.

