

CRYSTORAMA

1958

95 Cantiague Rock Road , Westbury NY 11590



ph: 516.931.9090 fax: 516.931.1254

info@crystorama.com, www.crystorama.com

MODEL#: 5791-AB ASSEMBLY AND DRESSING INSTRUCTIONS



All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.



FIXTURE ASSEMBLY, MOUNTING, AND WIRING INSTRUCTIONS:

1. Carefully remove the fixture out of the carton and check that all parts are included, referring to the above illustration. Make sure that the electricity is turned off.
2. Thread 2 Mounting screws properly into the relevant mounting holes pre-drilled on the Cross bar;
3. Attach the Cross bar to outlet box using 2 Outlet box screws upwards;
4. Make wire connections:
 - Attach ground wire to house ground wire using a wire nut (or attach them to the cross bar with a green ground screw).
 - Attach ribbed wire from light to white wire from power source with a wire nut.
 - Attach smooth wire from light to black wire from power source with a wire nut.
5. Tuck the wire connection neatly into the outlet box;
6. Attach the fixture body to the ceiling and let the 2 mounting screws protrude through the 2 pre-drilled keyholes on the Canopy, and fix it in place by finials;
7. Turn power on at fuse or circuit box.

When install the fixture :

1. Thread nipple into coupling,then slide the center tube,check ring,wheel,canopy, lock washer onto nipple,and secure them with hex nut;
2. Install the arm through housing using hex nut,then slide the rubber washer,glass shade,steel washer,onto nipple(1),and secure them with hex nut,thene slide the housing of the arm,hex nut ,cap onto nipple(1),and secure them with finial;
3. Install the ring onto glass shade;
4. Put the candle sleeve onto socket;
5. The fixture is ready for lamping and installation!