Prange & Co. Electric

Dimmer

120VAC, 60 Hz

For control of permanently-installed light fixtures only. Compatible with dimmable incandescent, CFL & LED bulbs. ELV compliant.

CAUTION: To reduce the risk of overheating and possible damage to other equipment, do not install to control a receptacle, a motor-operated appliance, a fluorescent lighting fixture, or a transformer supplied appliance.

WARNING: Shock Hazard. May result in serious injury or death. Before starting installation, switch power OFF at the source to all supply lines feeding the dimmer wall box.

Only a qualified electrician should perform this installation. Install in accordance with all national and local electrical codes.

Important Wiring Notes:

Install using copper wire only. For supply connection, use wires rated minimum 75°C. The supplied wire connectors are suitable for copper wire connections only. Follow the recommended striplengths and combinations for the supplied wire connectors.

Important - Wattage De-Rating Table

Bulb Type	Multi-Dimmer Installation / Application	501300-CL	503300-CL	sp1600-Cl	sb3600-Cl	PD1300-Cl	PD3300-Q	PD1600-CI	PD3600-Cl
Incandescent	single gang	300 Watts	300 Watts	600 Watts	600 Watts	300 Watts	300 Watts	600 Watts	600 Watts
Incandescent	2 gang	300 Watts	300 Watts	550 Watts	550 Watts	300 Watts	300 Watts	550 Watts	550 Watts
Incandescent	3 gang	300 Watts	300 Watts	450 Watts	450 Watts	300 Watts	300 Watts	450 Watts	450 Watts
Dimmable CFL / LED /ELV	single gang	240 Watts							
Dimmable CFL / LED /ELV	2 gang	240 Watts							
Dimmable CFL / LED /ELV	3 gang	240 Watts							

	Models					
	600 Watt	300 Watt				
	SD1600-CL	SD1300-CL				
cU	SD3600-CL	SD3300-CL				
LIST	PD1600-CL	PD1300-CL				
E352	PD3600-CL	PD3300-CL				

