

# INSTALLATION INSTRUCTION FOR 5171

## For Wall Mount Light Fixtures

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .**  
**AVERTISSEMENT! COUPER LE COURANT AU NIVEAU DES FUSIBLES OU DUDISJONCTEUR.**

READ AND SAVE THESE INSTRUCTIONS

### PREPARATION

1. Shut off the power at the fuse box or circuit breaker. If necessary, remove the old fixture, including the mounting hardware.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any parts necessary for installation.

### MOUNTING THE FIXTURE (Fig.1)

3. Secure hanging bracket (A) to outlet box with junction box screws (B) (Size: #8-32\*0.6"L). The side of the hanging bracket marked "GND" must face out.

### CONNECTING THE WIRES (Fig. 2)

4. Connect the fixture wires to the junction box wires as shown in Fig. 2. Make sure all wire connectors are secure. If there is no green ground wire from the junction box, connect the fixture ground wire to the circular strap with the green screw provided. Tuck these wire connections neatly into the wall junction box.

### COMPLETING THE INSTALLATION

5. Mount the mounting back plate (D) to hanging bracket (A), and then secure with mounting screws (C) (Size: #8-32\*0.3"L).
6. Place glass (F) over socket (E), then secure with socket ring (G) by wrench (H).
7. Install the light bulb (I) in accordance with the fixture's specifications.

**DO NOT EXCEED THE SPECIFIED WATTAGE!**  
**(NE PAS DEPASSER LA PUISSANCE NOMINALE MAXIMALE!)**

Return the power to the junction box and test the fixture. Your installation is now complete.

